

Accessories



MODEL : ACC-3WC

3 Way Gauge Cocks

Using Gauge cock is an economical method for isolating the pressure instrument from the process fluid. Generally used for low pressure Application below 25 kg/cm2(g).

3 Way Gauge Cock provides isolation of the instrument as well as vent (drain).

Normally available in CS, SS304 & SS316. Standard connection is 1/2" NPT(M) threads at process side and 1/2" NPT(F) at instrument & drain sides (other connections available on request)



Three Way Gauge Cock

Ordering Information

MODEL

ACC- [] [] [] [] [] []

ITEM DESCRIPTION
3WC 3 Way Gauge Cock

MATERIAL
CST Carbon Steel
S4S SS 304
S6S SS 316
XXX Other (Please specify)

INSTRUMENT CONNECTION
Please Select from following table

PROCESS CONNECTION
Please Select from following table

OPTION
NAC NACE
OXY O2 Cleaning
L Nil
XXX Other (Please specify)

DRAIN CONNECTION
Please Select from following table

CONNECTION							
Conn Thread	Code T	Size	Code	Type	Code	MALE / FEMALE	Code
		1/4"	06	NPS	NS	Male	M
		3/8"	10	NPT	NT	Female	F
		1/2"	15	BSP	BP		
		3/4"	20	BSPT	BT		
		1"	25	JIS-PF	PF		
		M20	M20	JIS-PT	PT		
				Gas	GS		
				R	RR		
				Rp	RP		
				Pitch 1.5	C		

e.g. For 1/2"NPT(M), Code: **T15NTM** For M20x1.5 (F), Code: **TM20CF**

Note: This catalogue indicates the general specifications used for most of the process applications. Any other specification not appearing here also can be provided as per customer requirement.

Sample Model Code: ACC-3WC-S6S-T15NTF-T15NTM-T15NTF-L